



SECTION 1. PRODUCT/ MIXTURE AND COMPANY IDENTIFICATION

1.1 Product Identifier	
Product name	BLANCONE® CLICK+
Other means of identification	Not Available

1.2 Details of the supplier of the safety data sheet		
Manufacturer/Supplier	IDS SpA	
Address	Via S. Cristoforo 28/10 – 17100 Savona - Italy	
Telephone	+39.019.862080	
Fax	-	
Website	Idsdental.it	
Email	info@idsdental.it	
Emergency Telephone	+39.019.862080	

1.3 Description of the Product

BLANCONE® CLICK+ is a product for teeth bleaching in office by dental professional. It is packaged in a dual chamber syringe which contains the whitening gel and the photo booster. The 2 gels are mixed automatically during the application from a special mixing tip.

SECTION 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Precautionary statement(s) Prevention

H372 Specific target organ toxicity - repeated exposure, Oral (Category 1), Thyroid H412 Harmful to aquatic life with long lasting effects (Category 3)

Not classified as Dangerous Goods for transport purposes.

Classification according to regulation (EC) No 1272/2008 [CLP] [1]	Eye Irritation Category 2
[1]	Classification drawn from EC Directive 1272/2008 - Annex VI

2.2 Label element(s)	
CLP label element	
Pictogram GHS07	
SIGNAL WORD	WARNING
Hazard statement(s)	
H319 H315	Causes serious irritation on eye and skin
Supplementary statement(s)	
Not Applicable	

Safety Data Sheet



According to Regulation (EC) No 1272/2008 Revision 0: 25/04/2025

P280	Wear protective gloves/protecting clothing/eye protection/face protection	
Precautionary statement(s) Response	•	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P337+P313	If eye irritation persists: Get medical	
	advice/attention.	
Precautionary statement(s) Storage		
P273	Avoid release to the environment.	
Precautionary statement(s) Disposal		
P501	Dispose of in compliance with governmental regulation. (EC1975L0442-10/11/2003)	

2.3 Other hazards

Cumulative effects may result following exposure*.

May produce skin discomfort*.

REACH - Art.57-59: The mixture does not contain Substances of Very High Concern (SVHC) at the SDS print date.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Description

Bleaching gel for application on the teeth.

3.1 Substances

See section 3.2

3.2 Mixtures/ Chemical characterization

Mixture of carbamide peroxide, glycerine and propylene glycol

CAS	EC No	REACH No	Description	% w/w	Classification according to
No			_		Regulation EC No 1272/2008 (GLP)
124-	204-		Urea hydrogen	≤20	Oxidizing Solid Category 3, Metal
43-6	701-4		peroxide		Corrosion Category 1, Acute Toxicity
					(Oral) Category 4, Acute Toxicity
					(Inhalation) Category 4, Skin
					Corrosion/Irritation Category 1B,
					Serious Eye Damage Category 1;
					H272, H290, H302, H332, H314,
					H318 [1]
1310-	215-	01-	Sodium	< 0.01	Skin Corr.,Cat. 1B; H314
73-2	185-5	2119457892-	Hydroxide		
		27-XXXX			
122-	204-	01-	Phenoxyethanol	< 0.30	Acute Tox. 4; Eye Irrit. 2; H302, H319
99-6	589-7	2119488943-			
		21-XXXX			
7681-	231-	01-	Potassium Iodide	≤ 0.1%	Specific target organ toxicity -
11-0	659-4	2119906339-			repeated exposure, Oral (Category 1),
		35-XXXX			Thyroid, H372





57-55- 6	200- 338-0	01- 2119456809- 23-XXXX	Propylene Glycol	13.33	Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008
6381- 92-6	205- 358-3	01- 2119486775- 20-0000	Disodium EDTA	< 0.25	Acute Tox. 4; STOT RE 2; H332, H373

SECTION 4. FIRST AID MEASURES

General information

The intended use is for application for the patient at dental office.

Skin contact

Rinse with water.

Eye contact

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing

No risk at small doses at intended use. Rinse out mouth and then drink plenty of water. In case of high dose consult doctor.

SECTION 5. FREFIGHTING MEASURES

Suitable extinguishing agents

Water spray. Use fire extinguishing methods suitable to surrounding conditions.

For safety reasons unsuitable extinguishing agents

Water with full jet, CO2

Protective equipment

No special measures.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Person-related safety precautions

Wear protective equipment. Keep unprotected persons away. Dilute with plenty of water.

Measures for cleaning/collecting

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Measures for environmental protection (see section 12)

Dispose contaminated material as waste according to item 13.

SECTION 7. HANDLING AND STORAGE

Safety Data Sheet

Sp.A.

According to Regulation (EC) No 1272/2008 Revision 0: 25/04/2025

Handling

Safe Handling

- Avoid all personal contact, including inhalation.
- ➤ Wear protective clothing when risk of exposure occurs.
- > Use in a well-ventilated area.
- > Prevent concentration in hollows and sumps.
- > DO NOT enter confined spaces until atmosphere has been checked.
- > DO NOT allow material to contact humans, exposed food or food utensils.
- Avoid contact with incompatible materials.
- ➤ When handling, DO NOT eat, drink or smoke.
- > Keep containers securely sealed when not in use.
- > Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- > Work clothes should be laundered separately. Launder contaminated clothing before re-use.
- ➤ Use good occupational work practice.
- ➤ Observe manufacturer's storage and handling recommendations contained within this SDS.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

Information about fire - and explosion protection

Ensure good ventilation/exhaustion at the workplace. No special measures required.

Storage

Requirements to be met by storerooms and receptacles

Store in dry and well-ventilated area at 5°C to 25°C. Avoid the direct contact with light and heat.

Information about storage in one common storage facility

- > Store away from flammable substances.
- > Store away from reducing agents.
- > Store away from metals.

Further information about storage conditions

- ➤ Keep receptacle tightly sealed.
- > Protect from heat and direct sunlight.
- > Store in a cool place.
- ➤ Heat will increase pressure and may lead to the receptacle bursting.

SECTION 8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

General protective measures

Avoid contact with eyes and skin.

Safety Data Sheet



According to Regulation (EC) No 1272/2008 Revision 0: 25/04/2025

Hygienic measures

Immediately remove all soiled and contaminated clothing

8.1 Control parameters				
Exposure limits (EH40)				
CAS No	Substance	TEEL-1*	TEEL-2*	TEEL-3*
-	Urea peroxide	1.2 mg/m3	13mg/m3	79 mg/m3

*TEEL-3 is the airborne concentration (expressed as ppm [parts per million] or mg/m³ [milligrams per cubic meter]) of a substance above which it is predicted that the general population, including susceptible individuals, when exposed for more than one hour, could experience life-threatening adverse health effects or death.

*TEEL-2 is the airborne concentration (expressed as ppm or mg/m³) of a substance above which it is predicted that the general population, including susceptible individuals, when exposed for more than one hour, could experience irreversible or other serious, long-lasting, adverse health effects or an impaired ability to escape.

*TEEL-1 is the airborne concentration (expressed as ppm or mg/m³) of a substance above which it is predicted that the general population, including susceptible individuals, when exposed for more than one hour, could experience notable discomfort, irritation, or certain asymptomatic, nonsensory effects. However, these effects are not disabling and are transient and reversible upon cessation of exposure.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

BLANCONE CLICK+ WHITENING GEL

Form: Gel

Colour: OPAQUE

Odour: Characteristic

	Value	Temperature
pН	4.0-6.0	
Boiling point	n/a	
Vapor pressure	n/a	20°C
Density	1.02-1.30 g/cm3	20°C
Solubility in water	Yes	
Viscosity	10,000-30,000 cPs	20°C





BLANCONE CLICK+ PHOTO BOOSTER GEL

Form: Gel

Colour: ORANGE-RED

Odour: Characteristic

	Value	Temperature
pН	5.2-7.5	
Boiling point	n/a	
Vapour pressure	n/a	20°C
Density	1.100-1.350 g/cm3	20°C
Solubility in water	Yes	
Viscosity	15,000-35,000 cPs	20°C

BLANCONE CLICK+ AFTER MIXING GEL

Form: Gel

Colour: ORANGE - RED

Odour: Characteristic

	Value	Temperature
рН	5-7	
Boiling point	n/a	
Vapor pressure	n/a	20°C
Density	1.020-1.350 g/cm3	20°C
Solubility in water	Yes	

SECTION 10. STABILITY AND REACTIVITY

StabilityProduct is stable at room temperature in closed containers under normal storage and handling conditions.

Dangerous reactions

Reacts with various metals

Reacts with reducing agents Reacts with catalysts

Acts as an oxidizing agent on organic materials such as wood, paper and fats

Hazardous decomposition products

Decomposition by combustion may release oxides of carbon and nitrogen.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects



Safety Data Sheet
According to Regulation (EC) No 1272/2008
Revision 0: 25/04/2025

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract. Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting
Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating. animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g. liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant.
Skin contact	Limited evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis. Open cuts, abraded or irritated skin should not be exposed to this material. Entry into the bloodstream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. IRRITANT
Eye	Evidence exists, or practical experience predicts, that the material may cause eye irritation in a substantial number of individuals and/or may produce significant ocular lesions. Repeated or prolonged eye contact may cause inflammation characterised by temporary redness (similar to windburn) of the conjunctiva (conjunctivitis). Temporary impairment of vision and/or other transient eye damage/ulceration may occur. STRONG IRRITANT WITH DANGER OF SEVER EYE INJURY
Chronic	Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.
Toxicity	No data available
Teratogenicity	No data available





Reproductive Effects	No data available	
Mutagenicity	No data available	

SECTION 12. ECOLOGICAL/ENVIROMENTAL INFORMATION

Under normal and foreseeable uses, there are no concerns for aquatic organisms exposed to product ingredients at the anticipated environmental concentrations. Relevant environmental data have been reviewed, and these indicate that the product is compatible with down-the-drain disposal routes, including municipal wastewater treatment processes and septic tank systems. This product is intended for dispersive use and should not be disposed of directly into the environment.

SECTION 13. DISPOSAL CONSIDERATIONS

Product	Small amounts may be diluted with plenty of water and washed away. Dispose of bigger amounts in accordance with Local Authority requirements.	
Uncleaned packaging	Empty contaminated packaging thoroughly. They may be recycled after thorough and proper cleaning. Recommended cleansing agents: Water, if necessary, together with cleansing agents.	
Waste treatment options	Not Available	
Sewage disposal options	Not Available	

SECTION 14. TRANSPORT INFORMATION

14.1 Labels Required	
Marine Pollutant	NO
HAZCHEM	Not Applicable
14.2 General transport information	
Land transport ADR/RID (GGV SE)	No dangerous good in sense of these transport regulations
Inland waterways transport (ADN)	No dangerous good in sense of these transport regulations
Sea transport IMDG (GGV See)	No dangerous good in sense of these transport regulations
Air transport (ICAO)	No dangerous good in sense of these transport regulations

SECTION 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

UREA HYDROGEN PEROXIDE (124-43-6 IS FOUND ON THE FOLLOWING REGULATORY LISTS)





Safety Data Sheet
According to Regulation (EC) No 1272/2008
Revision 0: 25/04/2025

European Customs Inventory of Chemical	European Union - European Inventory of
Substances ECICS (English)	Existing Commercial Chemical Substances
	(EINECS) (English)

SECTION 16. OTHER INFORMATION

16.1 Full text Hazard (H) and Risk (R) codes (not classification of ready mixed product)		
H-phrases		
H225	Highly flammable liquid and vapour	
H271	May cause fire or explosion; strong oxidiser.	
H272	May intensify fire; oxidizer.	
H290	May be corrosive to metals.	
H301	Toxic if swallowed.	
H302	Harmful if swallowed	
H314	Causes severe skin burns and eye damage.	
H318	Causes serious eye damage	
H330	Fatal if inhaled.	
H332	Harmful if inhaled.	

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.